

## 01 | MAINTENANCE AND PREVENTION TIPS

To keep the original quality and beauty of the product, follow the maintenance suggestions below:

- Use a vacuum cleaner regularly, removing any abrasive product that may be on the floor;
- Place door mats at all the entrances of your house and in places close to bathrooms, sinks, utility areas, etc.;
- Before putting the furniture in its place, apply felt protection disks on the ends of the legs of chairs, tables and moving items;
- Be careful with old shoes that may scratch the floor;
- Even though the Triângulo Floors have a UV protection finish, protect your flooring from the sun rays. Intense exposure to sunlight may cause modifications on the original coloring;
- While cleaning the floor do not use oil based products (e.g. wax), ammonia, petroleum or any other abrasive (such as a domestic detergent). Clean it with a soft cloth lightly dampened with warm water or with a product destined to the cleaning of wood floors with finish.
- If any liquid is spilled on the floor, wipe it immediately with a dry cloth.

Engineered Hardwood Flooring can be installed over most properly prepared subfloors and are engineered to be dimensionally stable, making them suitable for installation over all grade levels where moisture conditions do not exist. See all information and installation guidelines below or contact Technical Services at 757-474-5755

### CAUTION: WOOD DUST

Cutting, sanding or machining wood products produces wood dust. While wood products are not hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200), the International Agency for Research on Cancer (IARC) and the State of California have classified wood dust as a human carcinogen.

**PROPOSITION 65 WARNING:** This product produces wood dust when cut, sanded or machined. Wood dust is considered a carcinogen by the State of California.

**Precautionary Measures:** Airborne wood dust can cause respiratory, skin and eye irritation. Power tools should be equipped with a dust collector. Use an appropriate NIOSH-designated dust mask. Avoid dust contact with skin and eyes.

**First Aid Measures in case of irritations:** In case of irritation flush eyes with water. If needed seek medical attention. If dermatitis occurs, seek medical attention.

**CWARNING! DO NOT MECHANICALLY CHIP OR PULVERIZE EXISTING RESILIENT FLOORING, BACKING, LINING FELT, ASPHALTIC "CUTBACK" ADHESIVES OR OTHER ADHESIVES.**

Previously installed resilient floor covering products and the asphaltic or cutback adhesives used to install them may contain either asbestos fibers and/or crystalline silica. The products in this carton DO NOT contain asbestos or crystalline silica. Avoid creating dust. Inhalation of asbestos or crystalline dust is a cancer and respiratory tract hazard. Smoking by individuals exposed to asbestos fibers greatly increases the risk of serious bodily harm. Unless positively certain that the product is a non-asbestos containing material, you must presume it contains asbestos. Regulations may require that the material be tested to determine asbestos content and may govern the removal and disposal of material. See current edition of the Resilient Floor Covering Institute (RFCI) publication "Recommended Work Practices for Removal of Resilient Floor Coverings" for detailed information and instructions on removing all resilient covering structures.

### US SALES

757 420 4771  
SALES@TRIANGULO.COM.BR



@triangulo\_us



@triangulohardwoodfloors