Amazon Oak **Almond**

SPECIFICATIONS

ITEM NUMBER	ENGAMOAKAL51/4	ENGAMOAKAL71/2
THICKNESS	1/2" (12mm)	5/8" (16mm)
WIDTH	5.1/4" (131mm)	7.1/2" (190.5mm)
LENGTH	1" - 7"	1" - 7"
GLOSS	30%	8%
WEAR LAYER	3mm	3mm
CONTENT OF BOX	31,02 sqft	27,07 sqft
INSTALLATION	STAPLE, GLUE, FLOAT	STAPLE, GLUE, FLOAT

APPLICABLE STANDARDS

Adherence - At least 3 B (as standard norm ASTM D 3359 – 02);
Glue Bond (ANSI/HPVA EF 2002);
Formaldehyde emission - Less than 0.01ppm (ASTM D 6007 -2);
Total VOC (CA Specification 01350) - ≤ 0.5 mg/m3;
Critical radiant fluxe (Class 1) - 0,45watts/cm^2 (ASTM E648)

MADE IN BRAZIL

GREENGUARD
PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818
GOLD

CARB ULEF
(Ultra Low Emitting Formaldehyde)
Certified Manufacturer

CONTACT US!

Phone : +1 (757) 420 4771
Fax : +1 (757) 420 4772
Email : sales@triangulo.com.br

Know more,
click here:

triangulo.us

TRIÂNGULO®
Hardwood Floors