

AMAZON OAK PARIS

SPECIFICATIONS

ITEM NUMBER	ENGAMOAKPA71/2
THICKNESS	5/8" (16mm)
WIDTH	7.1/2" (190mm)
LENGTH	1'-7.2' RL (305-2200mm)
GLOSS	10%
CONTENT OF BOX	27,07 sqft

SPECIE	Amazon Oak
JANKA HARDNESS	1945 (pound force)
ORIGEN	Brazil - Sustainable Management
QUALITY	1st quality, natural color variation, free of structural defects.
FINISH	9 layers of transparent Polyurethane UV Finish.
STAIN	Water base stain.
CONTENT OF HUMIDITY	6% - 9%
INSTALATION	Staple, Glue, Float.
SUBFLOOR USAGE	Wood, Concrete. Radiant Heat Compatible - Yes Residential or Commercial.
WARRANTY	25 Years residential - 5 light commercial

Adherence - At least 3 B (as standard norm ASTM D 3359 – 02);
 Glue Bond (ANSI/HPVA EF 2002);
 Formaldehyde emission - Less than 0.01ppm (ASTM D 6007 -2);
 Total VOC (CA Specification 01350) - ≤ 0.5 mg/m3;
 Critical radiant fluxe (Class 1) - 0,45watts/cm² (ASTM E648)

CERTIFICATIONS



The mark of responsible forestry

Own Forest FSC Certified.



CLICK HERE!



+1 (757) 420 4771
 +1 (757) 420 4772
 SALES@TRIANGULO.COM.BR
 WWW.TRIANGULO.US
 INSTAGRAM: @TRIANGULO_HARDWOOD