

BRAZILIAN TEAK

SPECIFICATIONS

ITEM NUMBER	ENGBRAOAKKA71/2	ENGBT31/4 L
THICKNESS	1/2" (12mm)	1/2" (12mm)
WIDTH	5.1/4" (131mm)	3.1/4" (82.55mm)
LENGTH	1'-7.2' RL (305-2200mm)	1'-7.2' RL (305-2200mm)
GLOSS	30%	30%
CONTENT OF BOX	31.02sqft (2.882 sqm)	29.32 sqft

ENGBT31/4	ENGBT71/2
3/8" (9.5mm)3.1/4" (82.55mm)	5/8" (16mm) 7 1/2" (190,5mm)
1'-7.2' RL (305-2200mm)	1'-7.2' RL (305-2200mm)
30%	10%
19.52 sqft	27.1 sqft (2.515 sqm)

SPECIE	Brazilian Teak
JANKA HARDNESS	3540 (pound force)
ORIGEN	Brazil - Sustainable Management
QUALITY	1st quality, natural color variation, free of structural defects.
FINISH	9 layers of transparent Polyurethane UV Finish.
STAIN	Water base stain.
CONTENT OF HUMIDITY	6% - 9%
INSTALATION	Staple, Glue, Float.
SUBFLOOR USAGE	Wood, Concrete. Radiant Heat Compatible - Yes Residential or Commercial.
WARRANTY	25 Years residential - 5 light commercial

CERTIFICATIONS



Own Forest FSC
Certified.



Adherence - At least 3 B (as standard norm ASTM D 3359 – 02);
 Glue Bond (ANSI/HPVA EF 2002);
 Formaldehyde emission - Less than 0.01ppm (ASTM D 6007 -2);
 Total VOC (CA Specification 01350) - ≤ 0.5 mg/m3;
 Critical radiant flux (Class 1) - 0,45watts/cm² (ASTM E648)

CLICK HERE!



+1 (757) 420 4771
 +1 (757) 420 4772
 SALES@TRIANGULO.COM.BR
 WWW.TRIANGULO.US
 INSTAGRAM: @TRIANGULO_HARDWOOD