



CLASSICS COLLECTION

DATA SHEET SPECIFICATIONS

THICKNESS	1/2" (12mm)	5/8" (16mm)
WIDTH	5.1/4" (131mm)	7 1/2" (190,5mm)
LENGTH	1'-7.2' RL (305-2200mm)	1'-7.2' RL (305-2200mm)
GLOSS	30%	8%
CONTENT OF BOX	31.02sqft (2.882 sqm)	27.1 sqft (2.515 sqm)

SPECIES

- Amazon Oak (Pequi)
- Amendoim
- Brazilian Ash(Quaruba)
- Brazilian Cherry (Jatobá)
- Brazilian Chestnut (Sucupira)
- Brazilian Pecan (Guajuvira)
- Brazilian Teak (Cumaru)
- Manoa Oak (Angelim)
- Tigerwood (Muiracatiara)

ORIGEN	Brazil - Sustainable Management
QUALITY	1st quality, natural color variation, free of structural defects.
FINISH	9 layers of transparent Polyurethane UV Finish with Aluminum Oxide.
STAIN	Water base stain.
INSTALATION SUBFLOOR	Staple, Glue, Float. Wood, Concrete.
RADIANT HEAT COMPATIBLE	Amendoim, Amazon Oak, Braz. Pecan, Braz. Oak, Braz. Ash, Tigerwood.
USAGE	Residential or Commercial.
WARRANTY	25 Years residential - 5 light commercial
JANKA HARDNESS	Amazon Oak 1945 Amendoim 1912 Brazilian Ash 1570 Brazilian Cherry 2820 Brazilian Chestnut 3200 Brazilian Pecan 1920 Brazilian Teak 3540 Manoa Oak 1830 Tigerwood 2160

CERTIFICATIONS



The mark of responsible forestry
Own FSC Forest
Certified.



Highest protection against bacteria for clinically clean surfaces.

- Adherence - At least 3 B (ASTM D 3359 – 02);
- Glue Bond (ANSI/HPVA EF 2002);
- Formaldehyde emission - Less than 0.01ppm (ASTM D 6007 -2);
- Total VOC (CA Specification 01350) - ≤ 0.5 mg/m³;
- Critical radiant flux (Class 1) - 0,45watts/cm² (ASTM E648)
- Antimicrobial Surface - Approved: ISO 22196, ASTM G21-15, ASTM E2180-07



TRIÂNGULO®
Hardwood Floors

CLICK HERE!



+1 (757) 420 4771
+1 (757) 420 4772
SALES@TRIANGULO.COM.BR
WWW.TRIANGULO.US