

# BRAZILIAN ASH ATELIER

## SPECIFICATIONS

ITEM NUMBER	ENGBRASHAT51/4	ENGBRASHAT71/2
THICKNESS	1/2" (12mm)	5/8" (16mm)
WIDTH	5.1/4" (131mm)	7.1/2" (190mm)
LENGTH	1'-7.2' RL (305-2200mm)	1'-7.2' RL (305-2200mm)
GLOSS	30%	10%
CONTENT OF BOX	31.02sqft ( 2.882 sqm)	27,07 sqft

SPECIE	Brazilian Ash
JANKA HARDNESS	1570 (pound force)
ORIGEN	Brazil - Sustainable Management
QUALITY	1st quality, natural color variation, free of structural defects.
FINISH	9 layers of transparent Polyurethane UV Finish.
STAIN	Water base stain.
CONTENT OF HUMIDITY	6% - 9%
INSTALATION	Staple, Glue, Float.
SUBFLOOR USAGE	Wood, Concrete. Radiant Heat Compatible - Yes Residential or Commercial.
WARRANTY	25 Years residential - 5 light commercial

Adherence - At least 3 B (as standard norm ASTM D 3359 – 02);  
 Glue Bond (ANSI/HPVA EF 2002);  
 Formaldehyde emission - Less than 0.01ppm (ASTM D 6007 -2);  
 Total VOC (CA Specification 01350) - ≤ 0.5 mg/m3;  
 Critical radiant fluxe (Class 1) - 0,45watts/cm<sup>2</sup> (ASTM E648)

## CERTIFICATIONS



The mark of  
 responsible forestry

Own Forest FSC  
 Certified.



CLICK HERE!



+1 (757) 420 4771  
 +1 (757) 420 4772  
 SALES@TRIANGULO.COM.BR  
 WWW.TRIANGULO.US  
 INSTAGRAM: @TRIANGULO\_HARDWOOD