

TIGERWOOD

SPECIFICATIONS

| ITEM NUMBER | ENGTW51/4 | ENGTW31/4 L | ENGTW71/2 |
|----------------|-------------------------|-------------------------|-------------------------|
| THICKNESS | 1/2" (12mm) | 1/2" (12mm) | 5/8" (16mm) |
| WIDTH | 5.1/4" (131mm) | 3.1/4" (82.55mm) | 7.1/2" (190mm) |
| LENGTH | 1'-7.2' RL (305-2200mm) | 1'-7.2' RL (305-2200mm) | 1'-7.2' RL (305-2200mm) |
| GLOSS | 30% | 30% | 10% |
| CONTENT OF BOX | 31.02sqft (2.882 sqm) | 29.32 sqft | 27,07 sqft |

| | |
|---------------------|--|
| SPECIE | Brazilian Tigerwood |
| JANKA HARDNESS | 2160 (pound force) |
| ORIGEN | Brazil - Sustainable Management |
| QUALITY | 1st quality, natural color variation, free of structural defects. |
| FINISH | 9 layers of transparent Polyurethane UV Finish. |
| STAIN | Water base stain. |
| CONTENT OF HUMIDITY | 6% - 9% |
| INSTALATION | Staple, Glue, Float. |
| SUBFLOOR USAGE | Wood, Concrete. Radiant Heat Compatible - Yes Residential or Commercial. |
| WARRANTY | 25 Years residential - 5 light commercial |

Adherence - At least 3 B (as standard norm ASTM D 3359 – 02);
 Glue Bond (ANSI/HPVA EF 2002);
 Formaldehyde emission - Less than 0.01ppm (ASTM D 6007 -2);
 Total VOC (CA Specification 01350) - ≤ 0.5 mg/m3;
 Critical radiant fluxe (Class 1) - 0,45watts/cm² (ASTM E648)

CERTIFICATIONS



The mark of responsible forestry

Own Forest FSC Certified.



CLICK HERE!



+1 (757) 420 4771
 +1 (757) 420 4772
 SALES@TRIANGULO.COM.BR
 WWW.TRIANGULO.US
 INSTAGRAM: @TRIANGULO_HARDWOOD