

BRAZILIAN OAK VULKAN

SPECIFICATIONS

ITEM NUMBER	ENGBRAOAKVU71/2
THICKNESS	9/16" (14mm)
WIDTH	7.1/2" (190.5mm)
LENGTH	1 - 7' - (2,200mm)
GLOSS	8%
CONTENT OF BOX	31.58sqft (2.934sqm)

SPECIE	Brazilian Oak
JANKA HARDNESS	1466 (pound force)
ORIGEN	Brazil - Sustainable Management
QUALITY	1st quality, natural color variation, free of structural defects.
FINISH	9 layers of transparent Polyurethane UV Finish.
STAIN	Water base stain.
COLOR VARIATION	Medium-high variation
CONTENT OF HUMIDITY	6% - 9%
INSTALATION	Staple, Glue, Float.
SUBFLOOR USAGE	Wood, Concrete. Radiant Heat Compatible - Yes
WARRANTY	Residential or Commercial.
	25 Years residential - 5 light commercial

Adherence - At least 3 B (as standard norm ASTM D 3359 – 02);
 Glue Bond (ANSI/HPVA EF 2002);
 Formaldehyde emission - Less than 0.01ppm (ASTM D 6007 -2);
 Total VOC (CA Specification 01350) - \leq 0.5 mg/m³;
 Critical radiant flux (Class 1) - 0,45watts/cm² (ASTM E648)

NORDIC

Collection

BRAZILIAN OAK

Functional and very cozy, the Nordic line is one of the hottest trends in recent years. Our 12 colors mix light and dark tones in a durable matte finish. The extra wide planks follow the new trends in the industry.

CERTIFICATIONS



TRIÂNGULO US

+1 (757) 420 4771
 +1 (757) 420 4772
 SALES@TRIANGULO.COM.BR
 WWW.TRIANGULO.US
 INSTAGRAM: @TRIANGULO_HARDWOOD